

## **BOLIDTOP® 200 RF**

### **CHARACTERIZATION**

This antiskid floor finish system can be acquired at low initial costs due to its layer thickness. The quartz granules incorporated in the pigmented compound produce a wear-resistant result. The system is seamless, durable, impermeable to fluids, low maintenance and applied on site by own specialists.

### **PROPERTIES**

Bolidtop 200 RF is a floor finish system based on two-component low-viscous synthetic resins that are low odour. This floor finish is antiskid due to the sparingly sprinkled quartzes. This flooring is not impacted by mechanical loads in the form of pallet trucks. Due to the limited layer thickness the texture of the base remains visible.

Bolidtop 200 RF is resistant to most common chemicals.

Bolidtop 200 RF can be cleaned with commonly available cleaning products, but preferably with the products that are marketed by Bolidt. Cleaning this system requires special attention because of its inherent texture.

### **APPLICATION**

The flooring system is very suitable for platforms, stairs, parking decks and rinsing areas. This synthetic flooring is often applied in new buildings and renovation projects.

### **COLOURS**

You can find the colours that Bolidtop 200 RF is available in through the online service at <http://colors.bolidt.com>. On request and on revised terms, it is possible to deviate from this colour range.

### **COMPOSITION**

The polymers that are used in this system are tolerant, low viscous and low odour. They are based on solvent-free synthetic resins. Bolidt Kunststoftoepassing develops and produces the products in accordance with ISO 9001:2000.

### **INSTALLATION**

Bolidtop 200 RF is processed in liquid form and has to be applied by experts. That is why Bolidtop 200 RF can only be installed by the application specialists who work with Bolidt or its certified partners.

### **BASE SURFACE**

The most suitable bases for Bolidtop 200 RF are sand-cement screed, concrete and anhydrite. These need to be in good condition: stable, dry, clean and degreased. A detailed description of these and other base surfaces can be requested separately.

### **SETTING**

Bolidtop 200 RF can be walked on after 24 hours and can be mechanically loaded after 48 hours. Full chemical setting is attained after 7 days at room temperature.

Bolidt Kunststoftoepassing B.V.  
Nijverheidsweg 37  
P.O.Box 131  
3340 AC Hendrik-Ido-Ambacht  
The Netherlands