

BOLIDTOP® 525

CHARACTERIZATION

This comfortable, walk-friendly floor finish creates surveyability through its matt surface and uniform colour scheme. Its viscous-elastic properties produce high wear resistance and a reduction in contact noise. The system is seamless, durable, impermeable to fluids, low maintenance and applied on site by own specialists.

PROPERTIES

Bolidtop 525 is an approx. 2 mm thick and seamless floor finish system based on two-component low-viscous synthetic resins. Bolidtop 525 has an even and smooth appearance and is scratch resistant. The viscous-elastic properties of Bolidtop 525 give this flooring a comfortable character. Bolidtop 525 is highly suitable for spaces with busy foot traffic. The system absorbs contact noise to an increased extent.

Bolidtop 525 has a decorative function if a choice is made from the colour range. Bolidtop 525 is resistant to most common chemicals.

Bolidtop 525 can be cleaned with commonly available cleaning products, but preferably with the products that are marketed by Bolidt.

APPLICATION

The flooring system is very suitable for offices, shops, hallways, entrance halls, inpatient accommodation, classrooms and canteens. This synthetic flooring is often applied in new buildings and renovation projects.

COLOURS

You can find the colours that Bolidtop 525 is available in through the online service at <http://colors.bolidt.com>. On request and on revised terms, it is possible to deviate from this colour range.

COMPOSITION

The polymers that are used in this system are tolerant, low viscous and low odour. They are based on solvent-free and waterborne synthetic resins. Bolidt Kunststofopassing develops and produces the products in accordance with ISO 9001:2000.

INSTALLATION

Bolidtop 525 is processed in liquid form and has to be applied by experts. That is why Bolidtop 525 can only be installed by the application specialists who work with Bolidt or its certified partners.

BASE SURFACE

The most suitable bases for Bolidtop 525 are sand-cement screed, concrete and anhydrite. These need to be in good condition: stable, dry, clean and degreased. A detailed description of these and other base surfaces can be requested separately.

SETTING

Bolidtop 525 can be walked on after 24 hours and can be mechanically loaded after 48 hours. Full chemical setting is attained after 7 days at room temperature.

Bolidt Kunststofopassing B.V.
Nijverheidsweg 37
P.O.Box 131
3340 AC Hendrik-Ido-Ambacht
The Netherlands