

BOLIDTOP® 550

CHARACTERIZATION

This flow-applied floor finish system is characterized by excellent flow properties and therefore also offers a solution for floor spaces under existing machines. This smooth flooring is very suitable for heavy forklift traffic and combines with the Bolidtop 700 series without a difference in level. The system is seamless, durable, impermeable to fluids, low maintenance and applied on site by own specialists.

PROPERTIES

Bolidtop 550 is an approx. 5 mm thick synthetic floor finish based on two-component hard synthetic resins that are low odour. The self-levelling Bolidtop 550 has a smooth surface structure due to its excellent flow properties and layer thickness. Due to its good adhesion to the substrate and its durability characteristic, this seamless system is suitable for forklift traffic and pallet transport.

Bolidtop 550 is resistant to most common chemicals. Bolidtop 550 is available in a broad range of colours.

Bolidtop 550 Deco can be cleaned with commonly available cleaning products, but preferably with the products that are marketed by Bolidt.

APPLICATION

The flooring system is very suitable for application in beverage production, (petro)chemical production and pharmacy. This synthetic flooring is often applied in new buildings and renovation projects.

COLOURS

You can find the colours that Bolidtop 550 is available in through the online service at <http://colors.bolidt.com>. On request and on revised terms, it is possible to deviate from this colour range.

COMPOSITION

The polymers that are used in this system are tolerant, low viscous and low odour. They are based on solvent-free and waterborne synthetic resins. Bolidt Kunststoftoepassing develops and produces the products in accordance with ISO 9001:2000.

INSTALLATION

Bolidtop 550 is processed in liquid form and has to be applied by experts. That is why Bolidtop 550 can only be installed by the application specialists who work with Bolidt or its certified partners.

BASE SURFACE

The most suitable bases for Bolidtop 550 are sand-cement screed, concrete and anhydrite. These need to be in good condition: stable, dry, clean and degreased. A detailed description of these and other base surfaces can be requested separately.

SETTING

Bolidtop 550 can be walked on after 24 hours and can be mechanically loaded after 48 hours. Full chemical setting is attained after 7 days at room temperature.

Bolidt Kunststoftoepassing B.V.
Nijverheidsweg 37
P.O.Box 131
3340 AC Hendrik-Ido-Ambacht
The Netherlands