

## **BOLIDTOP® 700 PT**

### **CHARACTERIZATION**

The carefully finished surface of this high-quality flooring with a terrazzo look guarantees the absence of pores. Hygiene aspects have been implemented to a very high standard. The mechanically compacted flooring can withstand heavy loads. Skirting is optionally available in the form of an on-site seamless vertical extension of the flooring. The system is seamless, durable, impermeable to fluids, low maintenance and applied on site by own specialists.

### **PROPERTIES**

Bolidtop 700 PT is an approx. 5 mm thick, mechanically compacted and seamless floor finish based on two-component low-viscous synthetic resins that are low odour. Special attention has been paid to the surface structure, which makes Bolidtop 700 PT ideal for hygienic applications. Bolidtop 700 PT has a terrazzo look and is highly shock, impact and pressure resistant. Bolidtop 700 PT has been developed for spaces, in which durability, hygiene, character and high mechanical loads converge. Bolidtop 700 PT is scratch proof and durable.

Bolidtop 700 PT is resistant to most common chemicals.

Bolidtop 700 PT can be cleaned well with commonly available cleaning products, but preferably with the products that are marketed by Bolidt.

### **APPLICATION**

The flooring system is very suitable for application in clean rooms, laboratories and the pharmaceutical industry. This synthetic flooring is often applied in new buildings and renovation projects.

### **COLOURS**

You can find the colours that Bolidtop 700 PT is available in through the online service at <http://colors.bolidt.com>. On request and on revised terms, it is possible to deviate from this colour range.

### **COMPOSITION**

The polymers that are used in this system are tolerant, low viscous and low odour. They are based on solvent-free and waterborne synthetic resins. Bolidt Kunststoftoepassing develops and produces the products in accordance with ISO 9001:2000.

### **INSTALLATION**

Bolidtop 700 PT is processed in liquid form and has to be applied by experts. That is why Bolidtop 700 PT can only be installed by the application specialists who work with Bolidt or its certified partners.

### **BASE SURFACE**

The most suitable bases for Bolidtop 700 PT are sand-cement screed, concrete and anhydrite. These need to be in good condition: stable, dry, clean and degreased. A detailed description of these and other base surfaces can be requested separately.

### **SETTING**

Bolidtop 700 PT can be walked on after 24 hours and can be mechanically loaded after 48 hours. Full chemical setting is attained after 7 days at room temperature.

Bolidt Kunststoftoepassing B.V.  
Nijverheidsweg 37  
P.O.Box 131  
3340 AC Hendrik-Ido-Ambacht  
The Netherlands