

BOLIDTOP® FIFTYFIFTY

CHARACTERIZATION

The modern and comfortable flooring system that livens up a space through the combination of two closely related colours. This system complements a contemporary minimalistic style. The system is seamless, durable, impermeable to fluids, low maintenance and applied on site by own specialists.

PROPERTIES

Bolidtop FiftyFifty is an approx. 2 mm thick seamless flooring system based on two-component viscous-elastic and low-odour synthetic resins. The combination of two closely related colours creates a lively effect. Bolidtop FiftyFifty is available in a large number of tones.

Bolidtop FiftyFifty slightly suppresses contact noise and is heat conductive. The system is highly suitable for busy foot traffic. Bolidtop FiftyFifty is applied in liquid form.

Bolidtop FiftyFifty can be cleaned with commonly available cleaning products, but preferably with the products that are marketed by Bolidt.

APPLICATION

The flooring system is very suitable for offices, shops, hallways, entrance halls, inpatient accommodation, classrooms and canteens. This synthetic flooring is often applied in new buildings and renovation projects.

COLOURS

You can find the colours that Bolidtop FiftyFifty is available in through the online service at <http://colors.bolidt.com>. On request and on revised terms, it is possible to deviate from this colour range.

COMPOSITION

The polymers that are used in this system are tolerant, low viscous and low odour. They are based on solvent-free and waterborne synthetic resins. Bolidt Kunststoftoepassing develops and produces the products in accordance with ISO 9001:2000.

INSTALLATION

Bolidtop FiftyFifty is processed in liquid form and has to be applied by experts. That is why Bolidtop FiftyFifty can only be installed by the application specialists who work with Bolidt or its certified partners.

BASE SURFACE

The most suitable bases for Bolidtop FiftyFifty are sand-cement screed, concrete and anhydrite. These need to be in good condition: stable, dry, clean and degreased. A detailed description of these and other base surfaces can be requested separately.

SETTING

Bolidtop FiftyFifty can be walked on after 24 hours and can be mechanically loaded after 48 hours. Full chemical setting is attained after 7 days at room temperature.

Bolidt Kunststoftoepassing B.V.
Nijverheidsweg 37
P.O.Box 131
3340 AC Hendrik-Ido-Ambacht
The Netherlands